GB|ACOUSTICS



PET PREMIUM

Product Data Sheet 20 March 2020

GBACOUSTICS

SUMMARY

Our PET Premium panel is a versatile surface liner that can be used for creative acoustic solutions where design is critical. Merging high-performance absorbency with a lightweight, slim profile it is the perfect panel for any space.

APPLICATION

Sectors	Commercial, Education, Home Theatre and Studio
Versatility	Decorative as well as functional - can be utilised as room divider, pinboard or for brand identity purposes
Fixing options	Adhesive, mechanical fixing or ceiling suspension

SPECIFICATIONS

Product Name	PET Premium		
Composition	100% Polyester Fibre Panel		
Dimensions	1200mm x 600mm (or customised)		
Thickness	9mm	12mm	24mm
Tolerance	(+/-10%)	(+/-10%)	(+/-10%)
Weight	1900gsm	2400gsm	4600gsm

FIRE RATINGS

Rating	EN13501-12007 Class B
--------	-----------------------

BS 476 Part 7 class 1Y fire rated

GB|ACOUSTICS

NRC

	Surface mount	+25mm Gap	+50mm Gap
9mm			0.8
12mm	-	-	0.8
24mm	0.75	0.85	0.90

ENVIRONMENTAL

Standards	ISO 900, ISO 14001 accredited Quality and Environmental Management Systems.
Material	100% polyester fibres, of which a minimum of 75% is post consumer recycled polyester fibre (from PET bottle-flake)
Other	This product does not contain chemical binders including formaldehyde, Offcuts and manufacturing waste is re-used or recycled wherever possible. Uncontaminated panels can be recycled.

FABRIC CARE

Instructions	Dust and dirt can be removed by dusting, vacuuming, or by using a soft cloth/sponge with a solution of carpet/upholstery shampoo
Recommendation	Use a soft, damp cloth and blot dry. Spot cleaner has been used with success for light soiling

COLOUR

The PET PREMIUM panels in 12mm and 24mm are available in 34 colours:





