


Technical Rider

Stage size min 8x6m if this is not possible please contact Steve



Kanalbelegung:

- | | | |
|----|------------|--|
| 1 | Kick | Audix D6 (own) |
| 2 | Snare | ATM350 (own) |
| 3 | HiHat | Condenser (to provide) |
| 4 | Rack Tom | ATM350 (own) |
| 5 | Floor Tom | ATM350 (own) |
| 6 | Free/Spare | |
| 7 | OH Left | Condenser (to provide) |
| 8 | OH Right | Condenser (to provide) |
| 9 | Bass | DI (own) |
| 10 | Guitar | SM57 or similar (to provide) |
| 11 | KEY L | DI (own) |
| 12 | KEY R | DI (own) |
| 13 | VOC Bass | SM58 or similar (to provide) |
| 14 | VOC Guit | SM58 or similar (to provide) |
| 15 | LEAD V L | XLR out on Fx Rack (own mic & FX Rack) |
| 16 | LEAD V R | XLR out on FX Rack (own mic & FX Rack) |

Monitoring:

- 1 IEM Bass (own)
- 2 2x Wedge (min 12/1" with Headroom) to provide
- 3 1x Wedge (12/1") to provide
- 4 IEM Keyboards (own)
- 5 IEM Drums (own)

If possible, please use the IEM channels as a stereo signal.

What we need:

- enough micro cables
- 2 short mic stand (HiHat/Guitar)
- 4 long stands with gallow (OH / Backing V)
- power supply at the marked locations
- an XLR cable from the keyboard to the drum for click

SPECIAL PLEASE READ:

The lead vocals are transmitted as a stereo signal including all effects. PLEASE do not use your own effects. Use the lead vocals as a true stereo signal with panning 100% left & 100% right

If you have any questions please contact Steve:

stephenwaldron@web.de

+49 173 35 79 20 5