



STORZ COUPLINGS Alu PN 16

Storz delivery hose couplings

Standard	Claws	ND Shank	Length	Art. Code	Material
52-C CH	66	40	70	ST52KA66DH40ALF	Alu PN 16
52-C DIN 14332	66	42	55	ST52KA66DH42ALF	Alu PN 16
52-C	66	45	68	ST52KA66DH45ALF	Alu PN 16
52-C DIN 14302/86202	66	52	55	ST52KA66DH52ALF	Alu PN 16
52-C CH	66	55	70	ST52KA66DH55ALF	Alu PN 16
65 NEN 3374	81	52	60	ST65KA81DH52ALF	Alu PN 16
65 NEN 3374	81	65	59	ST65KA81DH65ALF	Alu PN 16
65	81	65	100	ST65KA81DH65ALF	Alu PN 16
65 NEN 3374	81	75	65	ST65KA81DH75ALF	Alu PN 16
75-B	89	70	75	ST75KA89DH70ALF	Alu PN 16
75-B DIN 14303/86203	89	75	60	ST75KA89DH75ALF	Alu PN 16



Standard	Claws	ND Shank	Art. Code	Material
25-D	31	25,4	ST25KA31DS25ALF	Alu PN 16
52-C	66	32,4	ST52KA66DS32ALF	Alu PN 16
52-C	66	38,4	ST52KA66DS38ALF	Alu PN 16
52-C	66	50,4	ST52KA66DS50ALF	Alu PN 16
75-B	89	75,4	ST75KA89DS75ALF	Alu PN 16
110-A	133	100,3	ST110KA133DS100ALF	Alu PN 16





Storz suction hose couplings

Standard	Claws	ND Shank	Length	Art. Code	Material
25-D	31	13	53	ST25KA31SS13ALF	Alu PN 16
25-D Grooved shank	31	19	50	ST25KA31SSG13ALF	Alu PN 16
25-D DIN 14301	31	25	53	ST25KA31SS19ALF	Alu PN 16
32	44	25	65	ST32KA44SS25ALF	Alu PN 16
32	44	32	80	ST32KA44SS32ALF	Alu PN 16
38	51	32	90	ST38KA51SS32ALF	Alu PN 16
38	51	38	90	ST38KA51SS38ALF	Alu PN 16
45	59	45	72	ST45KA59SS45ALF	Alu PN 16
52-C	66	19	90	ST52KA66SS19ALF	Alu PN 16
52-C	66	25	90	ST52KA66SS25ALF	Alu PN 16
52-C	66	32	90	ST52KA66SS32ALF	Alu PN 16
52-C	66	38	90	ST52KA66SS38ALF	Alu PN 16
52-C	66	42	90	ST52KA66SS42ALF	Alu PN 16
52-C	66	45	90	ST52KA66SS45ALF	Alu PN 16
52-C	66	50	90	ST52KA66SS50ALF	Alu PN 16
52-C Grooved shank	66	51	90	ST52KA66SS51ALF	Alu PN 16
52-C DIN 14321	66	52	90	ST52KA66SS52ALF	Alu PN 16
52-C CH	66	55	120	ST52KA66SS55ALF	Alu PN 16
52-C	66	60	90	ST52KA66SS60ALF	Alu PN 16
65	81	38	90	ST65KA81SS38ALF	Alu PN 16
65	81	52	90	ST65KA81SS52ALF	Alu PN 16
65	81	65	100	ST65KA81SS65ALF	Alu PN 16
65	81	70	95	ST65KA81SS70ALF	Alu PN 16
75-B	89	52	125	ST75KA89SS52ALF	Alu PN 16
75-B	89	65	125	ST75KA89SS65ALF	Alu PN 16
75-B	89	70	125	ST75KA89SS70ALF	Alu PN 16
75-B DIN 14322	89	75	125	ST75KA89SS75ALF	Alu PN 16
75-B Steel shank	89	75	125	ST75KA89SSST75ALF	Alu PN 16
75-B Grooved shank	89	76	125	ST75KA89SSG76ALF	Alu PN 16
75-B	89	80	125	ST75KA89SS80ALF	Alu PN 16
75-B Steel shank	89	80	125	ST75KA89SS80ALF	Alu PN 16
90	105	90	140	ST90KA105SS90ALF	Alu PN 16
100	115	101	150	ST100KA115SS101ALF	Alu PN 16
110-A	133	90	170	ST110KA133SS90ALF	Alu PN 16
110-A	133	100	170	ST110KA133SS100ALF	Alu PN 16
110-A Steel shank	133	100	170	ST110KA133SSST100ALF	Alu PN 16
110-A Grooved shank	133	102	170	ST110KA133SSG102ALF	Alu PN 16
110-A DIN 14323	133	110	170	ST110KA133SS110ALF	Alu PN 16
125	148	125	197	ST125KA148SS125ALF	Alu PN 16
150 (3 claws)	160	150	180	ST150KA160SS150ALF	Alu PN 16





Storz-adaptors with female thread DIN ISO 228-1

Standard	Claws	Female thread	Art. Code	Material
25-D	31	G 1/2	ST25KA31F013ALF	Alu PN 16
25-D	31	G 3/4	ST25KA31F019ALF	Alu PN 16
25-D DIN 14306	31	G 1	ST25KA31F025ALF	Alu PN 16
25-D	31	G 1 1/4	ST25KA31F032ALF	Alu PN 16
32	44	G 1	ST32KA44F025ALF	Alu PN 16
32	44	G 1 1/4	ST32KA44F032ALF	Alu PN 16
38	51	G 1 1/4	ST38KA51F032ALF	Alu PN 16
38	51	G 1 1/2	ST38KA51F038ALF	Alu PN 16
38	51	G 2	ST38KA51F050ALF	Alu PN 16
45	59	G 1 1/2	ST45KA59F038ALF	Alu PN 16
45	59	G 2	ST45KA59F050ALF	Alu PN 16
52-C	66	G 3/4	ST52KA66F019ALF	Alu PN 16
52-C	66	G 1	ST52KA66F025ALF	Alu PN 16
52-C	66	G 1 1/4	ST52KA66F032ALF	Alu PN 16
52-C	66	G 1 1/2	ST52KA66F038ALF	Alu PN 16
52-C DIN 14307/86204	66	G 2	ST52KA66F050ALF	Alu PN 16
52-C	66	G 2 1/2	ST52KA66F063ALF	Alu PN 16
65	81	G 1 1/2	ST65KA81F038ALF	Alu PN 16
65	81	G 2	ST65KA81F050ALF	Alu PN 16
65 NEN 3374	81	G 2 1/2	ST65KA81F063ALF	Alu PN 16
65	81	G 3	ST65KA81F075ALF	Alu PN 16
75-B	89	G 2	ST75KA89F050ALF	Alu PN 16
75-B DIN 14308/86205	89	G 2 1/2	ST75KA89F063ALF	Alu PN 16
75-B	89	G 3	ST75KA89F075ALF	Alu PN 16
75-B Steel insert	89	G 3	ST75KA89F075ALF	Alu PN 16
90	105	G 3	ST90KA105F075ALF	Alu PN 16
100	115	G 4	ST100KA115F100ALF	Alu PN 16
110-A	133	G 4	ST110KA133F100ALF	Alu PN 16
110-A DIN 14309	133	G 4 1/2	ST110KA133F110ALF	Alu PN 16
110-A	133	G 5	ST110KA133F125ALF	Alu PN 16
125	148	G 4	ST125KA148F100ALF	Alu PN 16
125	148	G 5	ST125KA148F125ALF	Alu PN 16
150 (3 claws)	160	G 6	ST150KA160F150ALF	Alu PN 16



Storz-adaptors with male thread DIN ISO 228-1

Standard	Claws	Male thread	Art. Code	Material
25-D	31	G 1/2	ST25KA31M013ALF	Alu PN 16
25-D	31	G 3/4	ST25KA31M019ALF	Alu PN 16
25-D	31	G 1	ST25KA31M025ALF	Alu PN 16
32	44	G 1	ST32KA44M025ALF	Alu PN 16
32	44	G 1 1/4	ST32KA44M032ALF	Alu PN 16
38	51	G 1 1/4	ST38KA51M032ALF	Alu PN 16
38	51	G 1 1/2	ST38KA51M038ALF	Alu PN 16
52-C	66	G 3/4	ST52KA66M019ALF	Alu PN 16
52-C	66	G 1	ST52KA66M025ALF	Alu PN 16
52-C	66	G 1 1/4	ST52KA66M032ALF	Alu PN 16
52-C	66	G 1 1/2	ST52KA66M038ALF	Alu PN 16
52-C	66	G 2	ST52KA66M050ALF	Alu PN 16
52-C	66	G 2 1/2	ST52KA66M063ALF	Alu PN 16
65	81	G 1 1/2	ST65KA81M038ALF	Alu PN 16
65	81	G 2	ST65KA81M050ALF	Alu PN 16
65 NEN 3374	81	G 2 1/2	ST65KA81M063ALF	Alu PN 16
65	81	G 3	ST65KA81M075ALF	Alu PN 16
75-B	89	G 2	ST75KA89M050ALF	Alu PN 16
75-B	89	G 2 1/2	ST75KA89M063ALF	Alu PN 16
75-B	89	G 3	ST75KA89M075ALF	Alu PN 16
110-A	133	G 4	ST110KA133M100ALF	Alu PN 16
150 (3 claws)	160	G 6	ST150KA160M150ALF	Alu PN 16



Storz-adaptors with male thread DIN ISO 228-1 with metal sealing surface suitable for end caps with RD DIN 405

Standard	Claws	Male thread	RD DIN 405	Art. Code	Material
52-C DIN 14317	66	G 2	50 x 1/6	ST52KA66MC050ALF	Alu PN 16
65	81	G 2 1/2	60 x 1/6	ST65KA81MC063ALF	Alu PN 16
65 NEN 3374	81	G 3	60 x 1/6	ST65KA81MC075ALF	Alu PN 16
75-B DIN 14318	89	G 2 1/2	65 x 1/6	ST75KA89MC063ALF	Alu PN 16
110 A DIN 14319	133	G 4	105 x 1/4	ST110KA133MC100ALF	Alu PN 16



Storz-adaptors with female thread DIN ISO 228-1 with metal sealing surface suitable for end caps Rd DIN 405

Standard	Claws	Female thread	RD DIN 405	Art. Code	Material
52-C	66	G 2	50 x 1/6	ST52KA66FC050ALF	Alu PN 16
65	81	G 2	60 x 1/6	ST65KA81FC050ALF	Alu PN 16
65	81	G 2 1/2	60 x 1/6	ST65KA81FC063ALF	Alu PN 16
65	81	G 3	60 x 1/6	ST65KA81FC075ALF	Alu PN 16



End caps with triangular boss with gasket and chain. Suitable for Storz adaptors with metal sealing surface.

Standard	ID DIN 40	Art. Code	Material
52-C DIN 14317	Rd 50 x 1/6	ST52DC50ALF	Alu PN 16
65 NEN 3374	Rd 60 x 1/6	ST65DC60ALF	Alu PN 16
75-B DIN 14318	Rd 65 x 1/6	ST75DC65ALF	Alu PN 16
110-A DIN 14319	Rd 105 x 1/4	ST110DC105ALF	Alu PN 16



Storz clamp fittings swivelling with female and male threaded tail end DIN ISO 228-1

Standard	Claws		Thread	Length	Art. Code	Material
52-C	66	Female / K	G 1 1/2	45	ST52KA66FS038ALF	Alu PN 16
52-C	66	Female / K	G 2	68	ST52KA66FS050ALF	Alu PN 16
75-B	89	Female / K	G 2 1/2	49	ST75KA89FS063ALF	Alu PN 16
75-B	89	Female / K	G 3	80	ST75KA89FS075ALF	Alu PN 16
100	115	Female / K	G 4	78	ST100KA115FS100ALF	Alu PN 16
110-A	133	Female / K	G 4	68	ST110KA133FS100ALF	Alu PN 16
125	148	Female / K	G 4	78	ST125KA148FS100ALF	Alu PN 16
52-C	66	Male / AG	G 2	70	ST52KA66MS050ALF	Alu PN 16
75-B	89	Male / AG	G 2 1/2	40	ST75KA89MS063ALF	Alu PN 16
110-A	133	Male / AG	G 4	44	ST110KA133MS100ALF	Alu PN 16
125	148	Male / AG	G 4	56	ST125KA148MS100ALF	Alu PN 16



Storz blank caps

Standard	Claws		Art. Code	Material
25-D DIN 14310	31		ST25KA31DCALF	Alu PN 16
32	44		ST32KA44DCALF	Alu PN 16
38	51		ST38KA51DCALF	Alu PN 16
45	59		ST45KA59DCALF	Alu PN 16
52-C DIN 14311/86206	66		ST52KA66DCALF	Alu PN 16
65 NEN 33 74	81		ST65KA81DCALF	Alu PN 16
75-B DIN 14312	89		ST75KA89DCALF	Alu PN 16
90	105		ST90KA105DCALF	Alu PN 16
100	115		ST100KA115DCALF	Alu PN 16
110-A DIN 14313	133		ST110KA133DCALF	Alu PN 16
125	148		ST125KA148DCALF	Alu PN 16
150 (3 Claws)	160		ST150KA160DCALF	Alu PN 16



Storz blank caps with lock. Prevents unauthorised opening, includes chain and 2 keys.

Standard	Claws		Art. Code	Material
52-C	66		ST52KA66DCLALF	Alu PN 16
65	81		ST65KA81DCLALF	Alu PN 16
75-B	89		ST75KA89DCLALF	Alu PN 16
110-A	133		ST110KA133DCLALF	Alu PN 16





Reducers Storz to Storz

Standard	Claw 1	Claw 2	Art. Code	Material
38 / 25-D	51	31	STREDKA38VSKA25ALF	Alu PN 16
52-C / 25-D DIN 14341	66	31	STREDKA52VSKA25ALF	Alu PN 16
52-C / 32	66	44	STREDKA52VSKA32ALF	Alu PN 16
52-C / 38	66	51	STREDKA52VSKA38ALF	Alu PN 16
65 / 38	81	51	STREDKA65VSKA38ALF	Alu PN 16
65 / 52-C	81	66	STREDKA65VSKA52ALF	Alu PN 16
75-B / 52-C DIN 14342	89	66	STREDKA75VSKA52ALF	Alu PN 16
75-B / 65	89	81	STREDKA75VSKA65ALF	Alu PN 16
90 / 75-B	105	89	STREDKA90VSKA75ALF	Alu PN 16
100 / 75-B	115	89	STREDKA100VSKA75ALF	Alu PN 16
110-A / 52-C	133	66	STREDKA110VSKA52ALF	Alu PN 16
110-A / 65	133	81	STREDKA110VSKA65ALF	Alu PN 16
110-A / 75-B DIN 14343	133	89	STREDKA110VSKA75ALF	Alu PN 16
110-A / 75-B Steel insert	133	89	STREDKASK110VSKA75ALF	Alu PN 16
110-A / 100	133	115	STREDKA110VSKA100AI	Alu PN 16
125 / 100	148	115	STREDKA125VSKA100AI	Alu PN 16
125 / 110-A	148	133	STREDKA125VSKA110AI	Alu PN 16
150 / 110-A	160	133	STREDKA150VSKA110AI	Alu PN 16
150 - 125	160	148	STREDKA150VSKA125AI	Alu PN 16



Reducers Storz adaptor to flange. Flange acc. to DIN 2501 PN 16

Standard	Claws	Flange	Interlock	Art. Code	Material
25-D	31	DN 25	85	STREDKA25VSFL25ALF	Alu
52-C	66	DN 50	125	STREDKA52VSFL50ALF	Alu
52-C	66	DN 80	160	STREDKA52VSFL80ALF	Alu
65	81	DN 65	145	STREDKA65VSFL65ALF	Alu
75-B	89	DN 65	145	STREDKA75VSFL65ALF	Alu
75-B	89	DN 80	160	STREDKA75VSFL80ALF	Alu
75-B	89	DN 100	180	STREDKA75VSFL100ALF	Alu
100	115	DN 100	180	STREDKA100VSFL100AL	Alu
110-A	133	DN 100	180	STREDKA110VSFL100AL	Alu
110-A	133	DN 125	210	STREDKA110VSFL125AL	Alu
125	148	DN 125	210	STREDKA125VSFL125AL	Alu
150	160	DN 150	240	STREDKA150VSFL150AL	Alu
205 (PN 10)	220	DN 200	295	STREDKA205VSFL200AL	Alu





Elbows 90° and 45° Inlet swivel Storz adaptor outlet fixed Storz adaptor.
Elbow in malleable iron GTW galvanised Storz adaptors in aluminium.

Standard	Claws	Elbow	Art. Code	Material	
52-C	52-C	66	90°	STREDKA52EL9AL	Alu
52-C	52-C	66	45°	STREDKA52EL4AL	Alu
75-B	75-B	89	90°	STREDKA75EL9AL	Alu
75-B	75-B	89	45°	STREDKA75EL4AL	Alu
110-A	110-A	133	90°	STREDKA110EL9AL	Alu



Hose shut-off ball valves in aluminium for shut-off of fire hose-lines. Inlet and outlet with Storz adaptors.

Standard	Claws	Claws2	Art. Code	Material
52-C	52 C	52 C	STREDKA52KGAL	Alu PN 16
75-B	75 B	75 B	STREDKA75KGAL	Alu PN 16
110-A	110 A	110 A	STREDKA110KGAL	Alu PN 16



Suction strainers with non-return valve and discharge facility.

Size	Standard	Claws	Art. Code	Material
45	52-C	66	ST52STRAIN45AL	Alu
65	75-B	89	ST75STRAIN65AL	Alu
100	110-A	DIN 14 355	ST110STRAIN100AL	Alu



Wire mesh basket galvanised with quick closing device, prevents clogging of suction strainer.

Standard	Length	Wide	Art. Code	Size
52-C	235	235	ST52MESH235	95
75-B	290	290	ST75MESH290	100
110-A	340	340	ST110MESH340	125
125	340	340	ST125MESH340	125



Clappered and non clappered siamese with two or three inlets Connection Storz or threaded ends all in aluminium.

Storz entry	Storz exit	Art. Code	
2 x 52-C	75-B	ST75WEG2-C52AL	
2 x 75-B	110-A	DIN 14 355	ST110WEG2-75BAL
3 x 75-B	110-A	DIN 14 355	ST110WEG3-75BAL
52-C	52 C	without non return flap	ST52WEG2-52CAL
75-B	52 C	without non return flap	ST75WEG2-52CAL
110-A	75 B	without non return flap	ST110WEG2-75BAL

