

SERIES 2200

LIL' HOISTER LIFT

SUMNER

Just of few of the applications for the Lil' Hoister:

- HVAC compressor Installation
- Loading and unloading equipment and material from service vehicles
- Cabinet installation
- Lifting electrical trays
- Positioning pipe & ducts
- Installing air conditioners
- Handling machine parts & tooling
- Loading equipment in rental yards
- Hoisting small beams
- Positioning hospital TVs
- Hauling & lifting cement bags
- Installing appliances
- Removing electrical motors
- Installing light fixtures



2210 Lift (Part Number 784310)

The double-masted 2210 Lift offers the capability of lifting light fixtures or AC units in low ceiling buildings. Its forks fit between most acoustical ceiling tiles.

| | |
|--------------------------|--------|
| Height max. (forks up) | 3.4 m |
| Height max. (forks down) | 3.0 m |
| Lift capacity | 135 kg |
| Height stowed | 178 cm |
| Length stowed | 33 cm |
| Length operating | 104 cm |
| Width stowed | 66 cm |
| Width max | 79 cm |
| Winch cranks per ft/m | 24 |
| Basic weight | 49 kg |

Legs Extend for Greater Stability

Plunger pin action allows
quick adjustment.



Optional features available for Series 2200 Lifts

Aluminum Tray (part no. 784240)

Lightweight and rust free, this 18" x 22" (46 x 56 cm) aluminum tray slides on to forks and attaches quickly and safely with springloaded plunger pins.



Wheel Brake Kit (part no. 784218)

Easy to assemble brake kit for 8" (20 cm) wheels prevents lift from moving while being loaded. Recommended for use with the aluminum tray.



Dually Wheel Kit (part no. 784258)

Ideal for use on grass or dirt or when the lift is used as a hand truck.



Reversible Forks

Two plunger pins permit quick release of forks. Forks may be removed for storage or reversed for added height.

