

# Installation scenarios Ultrasonic armatures

For industrial applications and R&D


Type 5 – single port armatures

Date: September 2023



## 5 - single port armatures

#### **Application examples Probe examples Connection fittings** Particle manipulation: Ingold DN25/DN40 BlazeMetrics probes ATR-FTIR Spectroscopy **E&H** Raman probes GEA Varivent Type N or F Raman Spectroscopy Tornado Hudson Triclamp In-line Microscopy Marqmetrix Ballprobes Outer diameter DN19 Mettler Toledo ATR probes Comopatible probe diameters: Cleaning: ATR-FTIR Spectroscopy var. Hellma probes 6mm (1/4") Raman Spectroscopy 9,5mm (3/8") Inline Microscopy 12mm und 12,7mm (1/2") FBRM 14mm for outer diameter DN25 Additional compatible





The length L1 can be chosen before ordering.
With the DN25 variant, only the diameter of the ultrasonic fitting changes.



probe diameter:19mm (3/4")

Adaptations possible upon request.







#### Disclaimer:

The information, text and illustrations in this document are for informational purposes only. We strive to provide accurate and up-to-date information, but the accuracy, completeness or timeliness of the content is not warranted. We reserve the rights to make changes to the content at any time.

### Changes and Copyright:

All rights reserved. All trademarks and logos are the property of their respective owners.

Copying, reproducing or modifying any content of this document without express written permission is prohibited.

#### Further information:

Responsible for content and printing: usePAT GmbH, Austria

Copyright © 2023 usePAT GmbH, Vienna, Austria

#### usePAT GmbH

Schoenbrunner Strasse 231/2.01 1120 Vienna | Austria – Europe Phone: +43 660 83 45 674

E-mail: info@usePAT.com
Web: www.usePAT.com